

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK 5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

Test Item Description	
Manufacturer	EF Johnson Technologies
Manufacturer Contact	John Oblak (507) 382-6327
Product Name	TK5430 700/800 MHz Portable Subscriber Unit
Installed Options	P25 Conventional P25 Trunking DES Encryption AES Encryption
Vocoder Identification	Enhanced Full Rate

Test Description	
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance	
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	

Test Information	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)
Date(s) of Test	July 28, 2014 to August 4, 2014
Date of Issue	August 25, 2014

Test Information	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)
Date(s) of Test	July 28, 2014 to August 4, 2014
Date of Issue	August 25, 2014

Test Information	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)
Date(s) of Test	August 7, 2014
Date of Issue	August 20, 2014

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

Test Information	
P25 CAP Laboratory Code	P25CAP081017 (Harris Corporation)
Date(s) of Test	November 6, 2014
Date of Issue	November 10, 2014

Test Information	
P25 CAP Laboratory Code	P25CAP081011 (Compliance Testing, LLC)
Date(s) of Test	May 27, 2015
Date of Issue	June 2, 2015

Informative References	
Date	Title
Mar 2010	P25-CAB-CAI_TEST_REQ – March 2010

Other Devices Tested with TK 5430 Portable Subscriber Unit		
Manufacturer	Product Name, Definition, and Unique ID	Installed Options
EF Johnson	ATLAS Trunked Infrastructure	Release 1.1.0-10, TSNI 1.2.0-14
Harris Corp.	VIDA Premier SR10A MASTR V	Firmware R7G13
Codan Radio	Codan MT-4E – Daniels Trunked Radio	V1.1.0.9

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance		DTR-P25CAP081010-14082501	
Receiver Tests			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	≤ -116 dBm (Class A)	P1
2.1.5	Faded Reference Sensitivity	≤ -108 dBm (Class A)	P2
2.1.6	Signal Delay Spread Capability	≥ 50 μs	P3
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	P
2.1.9	Spurious Response Rejection	≥ 70 dB (Class A)	P
2.1.10	Intermodulation Rejection	≥ 70 dB (Class A)	P
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	P
2.1.17	Late Entry Unsquench Delay		
	No Talk Group or Encryption	≤ 125 ms	P
	Talk Group Only	≤ 370 ms	P
	Encryption Only	≤ 370 ms	P
	Both Talk Group and Encryption	≤ 460 ms	P
2.1.18	Receiver Throughput Delay	≤ 125 ms	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance		DTR-P25CAP081010-14082501	
Transmitter Tests (800 MHz)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	P
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	P
	Encoder Attack Time	≤ 100 ms	P
2.2.14	Transmitter Throughput Delay	≤ 125 ms	P
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	$2544 \text{ Hz} < f_{\text{dev}} \leq 3111 \text{ Hz}$	P
	Low Level Signal Deviation	$848 \text{ Hz} < f_{\text{dev}} \leq 1037 \text{ Hz}$	P
2.2.16	Modulation Fidelity	$\leq 5\%$ (Class A)	P
2.2.18	Transient Frequency Behavior		
	Time Interval $t_1 = 20$ ms	$\leq \pm 12.5$ kHz	P
	Time Interval $t_2 = 50$ ms	$\leq \pm 6.25$ kHz	P
	Time Interval $t_3 = 10$ ms	$\leq \pm 12.5$ kHz	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance		DTR-P25CAP081010-14082501	
Transmitter Tests (700 MHz)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio		
	Offset From Center Frequency (kHz)		
	9.375	40 dB	P
	15.625, 21.875, 37.5	60 dB	P
	62.5, 87.5, 150, 250, 350	65 dB	P
	>400 kHz to 12 MHz	75 dB	P
2.2.12	12 MHz to paired RX Band	75 dB	P
	In the paired RX Band	100 dB	P
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	P
2.2.14	Encoder Attack Time	≤ 100 ms	P
	Transmitter Throughput Delay	≤ 125 ms	P
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	2544 Hz < f _{dev} ≤ 3111 Hz	P
2.2.16	Low Level Signal Deviation	848 Hz < f _{dev} ≤ 1037 Hz	P
	Modulation Fidelity	≤ 5% (Class A)	P
2.2.18	Transient Frequency Behavior		
	Time Interval t ₁ = 20 ms	≤ ± 12.5 kHz	P
	Time Interval t ₂ = 50 ms	≤ ± 6.25 kHz	P
	Time Interval t ₃ = 10 ms	≤ ± 12.5 kHz	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-14082501 DTR-P25CAP081010-14082502	
Receiver Tests			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	≤ -116 dBm (Class A)	P1
2.1.5	Faded Reference Sensitivity	≤ -108 dBm (Class A)	P2
2.1.6	Signal Delay Spread Capability	≥ 50 μs	P3
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	P
2.1.9	Spurious Response Rejection	≥ 70 dB (Class A)	P
2.1.10	Intermodulation Rejection	≥ 70 dB (Class A)	P
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-14082501 DTR-P25CAP081010-14082502	
Transmitter Tests (800 MHz)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	P
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	P
	Encoder Attack Time	≤ 100 ms	P
2.2.14	Transmitter Throughput Delay	≤ 125 ms	P
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	$2544 \text{ Hz} < f_{\text{dev}} \leq 3111 \text{ Hz}$	P
	Low Level Signal Deviation	$848 \text{ Hz} < f_{\text{dev}} \leq 1037 \text{ Hz}$	P
2.2.16	Modulation Fidelity	$\leq 5\%$ (Class A)	P
2.2.18	Transient Frequency Behavior		
	Time Interval $t_1 = 20$ ms	$\leq \pm 12.5$ kHz	P
	Time Interval $t_2 = 50$ ms	$\leq \pm 6.25$ kHz	P
	Time Interval $t_3 = 10$ ms	$\leq \pm 12.5$ kHz	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-14082501 DTR-P25CAP081010-14082502	
Transmitter Tests (700 MHz)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio		
	Offset From Center Frequency (kHz)		
	9.375	40 dB	P
	15.625, 21.875, 37.5	60 dB	P
	62.5, 87.5, 150, 250, 350	65 dB	P
	>400 kHz to 12 MHz	75 dB	P
2.2.12	12 MHz to Paired RX Band	75 dB	P
	In the Paired RX Band	100 dB	P
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	P
2.2.14	Encoder Attack Time	≤ 100 ms	P
	Transmitter Throughput Delay	≤ 125 ms	P
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	2544 Hz < f _{dev} ≤ 3111 Hz	P
2.2.16	Low Level Signal Deviation	848 Hz < f _{dev} ≤ 1037 Hz	P
	Modulation Fidelity	≤ 5% (Class A)	P
2.2.18	Transient Frequency Behavior		
	Time Interval t ₁ = 20 ms	≤ ± 12.5 kHz	P
	Time Interval t ₂ = 50 ms	≤ ± 6.25 kHz	P
	Time Interval t ₃ = 10 ms	≤ ± 12.5 kHz	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance		DTR-P25CAP081010-14082501 DTR-P25CAP081010-14082502	
Trunked Subscriber Unit Tests			
Test Case	Description	Requirement	Results
2.3.1	Trunking Control Channel Slot Times (45 ms slot) Encode Attack Time RF Power Attack Time RF Power Turn Off Time	2.00 ms ≤ t ≤ 11.65 ms 0 ms ≤ t ≤ 11.65 ms ≤ 1.57 ms	P P P
2.3.2	Trunking Request Time	≤ 167.5 ms	P
2.3.3	Trunking Voice Access Time	500 ms (Manufacturer Specified)	P
2.3.5	Transmitter Time to Key on a Traffic Channel Short Channel Form	≤ 150.0 ms	P

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability		DTR- P25CAP081010- 14082001	DTR- P25CAP081017- 1141104K	DTR- P25CAP081011
EF Johnson TK 5430 Portable		EF Johnson IP25 Trunking Infrastructure	Harris VIDA Trunked Infrastructure	Codan
Test Case	Description			
2.2.1	Full Registration			
2.2.1.4.1	Test Case 1 - Valid Registration			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.1.4.2	Test Case 2 – Denied or Refused			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.1.4.3	Test Case 3 - Unverified Registration			
	Home Operation	P	P	N5
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.2	Group Voice Call			
2.2.2.4.1	Test Case 1 – Group Call Granted			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.2.4.2	Test Case 2 – Group Call Denied			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.2.4.3	Test Case 3 – Group Call Request			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability		DTR- P25CAP081010- 14082001	DTR- P25CAP081017- 1141104K	DTR-P25CAP081011
EF Johnson TK 5430 Portable		EF Johnson IP25 Trunking Infrastructure	Harris VIDA Trunked Infrastructure	Codan
Test Case	Description			
2.2.3	Unit-To-Unit Voice Call			
2.2.3.4.1	Test Case 1 – Unit-To-Unit Call With Target Availability Check			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.2	Test Case 2 – Unit-To-Unit Call Target Availability Check Denied By Target			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.3	Test Case 3 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment after target availability check			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.4	Test Case 4 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment before target availability check			
	Home Operation	N/A 1	N/A 1	N/A 1
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.5	Test Case 5 – Unit-To-Unit Call Without Target Availability Check			
	Home Operation	N2	P	N2
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability		DTR- P25CAP081010- 14082001	DTR- P25CAP081017- 1141104K	DTR-P25CAP081011
EF Johnson TK 5430 Portable		EF Johnson IP25 Trunking Infrastructure	Harris VIDA Trunked Infrastructure	Codan
Test Case	Description			
2.2.3	Unit-To-Unit Voice Call			
2.2.3.4.6	Test Case 6 – Unit-To-Unit Call Queued Without Target Availability Check			
	Home Operation	N2	P	N2
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.7	Test Case 7 – Unit-To-Unit Call Denied			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability		DTR- P25CAP081010- 14082001	DTR- P25CAP081017- 1141104K	DTR- P25CAP081011
EF Johnson TK 5430 Portable		EF Johnson IP25 Trunking Infrastructure	Harris VIDA Trunked Infrastructure	Codan
Test Case	Description			
2.2.4	Broadcast Voice Call			
2.2.4.4.1	Test Case 1 – Broadcast Voice Call			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.5	Affiliation			
2.2.5.4.1	<i>Test Case 1 - Radio Permitted To Affiliate With New Group</i>			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.5.4.2	<i>Test Case 2 - Radio Denied Affiliation To New Group</i>			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.6	Announcement Group Call			
2.2.6.4.1	Test Case 1 - Collection Of Talk Groups Receive Call			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.7	Emergency Alarm			
2.2.7.4.1	Test Case 1 - Emergency Alarm			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability		DTR- P25CAP081010- 14082001	DTR- P25CAP081017- 1141104K	DTR-P25CAP081011
EF Johnson TK 5430 Portable		EF Johnson IP25 Trunking Infrastructure	Harris VIDA Trunked Infrastructure	Codan
Test Case	Description			
2.2.8	Emergency Group Call			
2.2.8.4.1	Test Case 1 - Emergency Call			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.10	Encryption			
2.2.10.4.1	Test Case 1 - Call Privacy For Encrypted Call			
	Home Operation	P	P	P
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.11	Intra-Location Registration Area Roaming			
2.2.11.4.1	Test Case 1 – Idle Radio			
	Home Operation	P	P	N6
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4

Project 25 Compliance Assessment Program
 Summary Test Report
 EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
 STR-EFJ-15082803
 August 28, 2015

Model Class Definition		Applied to P25-CAB-CAI_Test_Req Mar 2010, 2.1.3.2	
Model Class Name	Product Name, Definition, and Unique ID	Installed Options	
TK 5430 Series Portable	TK 5430 Portable	Firmware:	K 1.11.01; Trunking, Encryption
		Firmware:	

Test Case Result Definitions	
No Test Performed	---
Test Does Not Apply to the Test Object	N/A
Test Object Meets Requirements	P (Pass)
Test Object Does Not Meet Requirements	F (Fail)
Test Object is Not Conclusive	I (Inconclusive)

Comments
N/A 1: Test case 2.2.3.4.4 is not applicable for these infrastructures; see results of test 2.2.3.4.3.
N1: EF Johnson infrastructure does not support Inter-System or Inter-WACN roaming.
N2: Test Cases 2.2.3.4.5 and 2.2.3.4.6 are not supported by EF Johnson and Codan FNE.
N3: Harris infrastructure does not support Inter-System or Inter-WACN roaming.
N4: Codan infrastructure does not support Inter-System or Inter-WACN roaming.
N5: Codan infrastructure does not support Test Case 3, Section 2.2.1.4.3 Unverified Registration
N6: Codan infrastructure does not support Intra-Location Registration Area Roaming, Test Case 1 Section 2.2.11.4.1
N7: TK 5430 meets timing requirements in the 45 ms slot timing mode.
P1: EF Johnson TK 5430 VHF subscriber passes Reference Sensitivity (≤ -116 dBm) specification for C4FM (Non-Simulcast) and Simulcast modulations.
P2: EF Johnson TK 5430 VHF subscriber passes Faded Reference Sensitivity (≤ -108 dBm) specification for C4FM (Non-Simulcast) and Simulcast modulations.
P3: EF Johnson TK 5430 VHF subscriber passes Signal Delay Spread Capability specification for C4FM (Non-Simulcast) (≥ 50 μ s) and Simulcast modulations (≥ 80 μ s).
P4: EF Johnson TK 5430 VHF subscriber passes Adjacent Channel Rejection (≥ 60 dB) specification for C4FM (Non-Simulcast) and Simulcast modulations.

Project 25 Compliance Assessment Program
Summary Test Report
EF Johnson TK5430 700/800 MHz Portable Subscriber Unit
STR-EFJ-15082803
August 28, 2015

The information contained herein has been provided by the manufacturer of the product with permission to make the information publicly available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS". DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute an endorsement by or recommendation from DHS.

OMB NO: 1640-0015

EXPIRATION DATE: 07/31/2015

Burden Statement

An agency may not consider or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and expiration date. The control number for this collection is 1640-0015 and this form will expire on 07/31/2015. The estimated average time to complete this form is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528.

DHS FORM 10044 – June 2009