#### **Test Item Description**

Manufacturer	EF Johnson Technologies	
Manufacturer Contact Randy O'Connor (972) 819-0911		
Product Name Viking VP6430F2/F3 700/800 Portable Subscriber Unit		
Installed Options	SEM Installed	
Vocoder Identification	Enhanced Full Rate	

#### **Test Description**

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability

#### **Laboratory Information**

Laboratory	Details
P25 CAP Laboratory Code P25CAP081010 (EF Johnson Technologies)	
Date(s) of Test	January 27, 2017 - March 10, 2017
Date of Issue	March 13,2017

Laboratory	Details	
P25 CAP Laboratory Code	Laboratory Code P25CAP081016 (TIMCO Engineering)	
Date(s) of Test	March 22, 2017	
Date of Issue	March 22, 2017	

Laboratory	Details	
P25 CAP Laboratory Code P25CAP081010 (EF Johnson Technologies)		
Date(s) of Test	May 12, 2017	
Date of Issue	June 14, 2017	

#### **Informative References**

Date	Title
Mar 2010	P25-CAB-CAI_TEST_REQ - March 2010

## Other Devices Tested with Viking VP6430F3/F2 Portable Subscriber Unit

Manufacturer Product Name, Definition, and Unique ID		Installed Options	
EF Johnson	ATLAS Trunked Infrastructure	TSNI 2.0.2.3	
Airbus / Tait	P25 Trunked Infrastructure TB5500i	EADS P25V11_06 E22	
Tait Limited	P25 Trunked Infrastructure TN9400	V1.12	
Motorola	ASTRO25 Trunked Infrastructure	System Release: ASTRO25 7.17	

## Receiver Tests (700/800 MHz) - Conventional

Test Identification	Detailed Test Report Identification	
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance	DTR-P25CAP081010-17031401	

Receiver Tests (700/800 MHz)			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	≤ -116 dBm (Class A	P1
2.1.5	Faded Reference Sensitivity	≤ -108 dBm (Class A)	P2
2.1.6	Signal Delay Spread Capability	≥ 50 µs	P3
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	Р
2.1.9	Spurious Response Rejection	≥ 80 dB (Class A)	Р
2.1.10	Intermodulation Rejection	≥ 75 dB (Class A)	Р
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	Р
2.1.17	Late Entry Unsquelch Delay		
	No Talk Group or Encryption	≤ 125 ms	Р
	Talk Group Only	≤ 370 ms	Р
	Encryption Only	≤ 370 ms	Р
	Both Talk Group and Encryption	≤ 460 ms	Р
2.1.18	Receiver Throughput Delay	≤ 125 ms	Р

# Transmitter Tests (800 MHz) - Conventional

Test Identification	Detailed Test Report Identification	
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance	DTR-P25CAP081010-17031401	

Transmitter Tests (800 MHz)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	Р
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	Р
	Encoder Attack Time	≤ 100 ms	Р
2.2.14	Transmitter Throughput Delay	≤ 125 ms	Р
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	2544 Hz < f <sub>dev</sub> ≤ 3111 Hz	Р
	Low Level Signal Deviation	$848~Hz < f_{dev} \leq 1037~Hz$	Р
2.2.16	Modulation Fidelity	≤ 5% (Class A)	Р
2.2.18	Transient Frequency Behavior		
	Time Interval t <sub>1</sub> = 20 ms	∆f  ≤ 12.5 kHz	Р
	Time Interval t <sub>2</sub> = 50 ms	∆f  ≤ 6.25 kHz	Р
	Time Interval t <sub>3</sub> = 10 ms	∆f  ≤ 12.5 kHz	Р

# Transmitter Tests (700 MHz) - Conventional

Test Identification	Detailed Test Report Identification	
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance	DTR-P25CAP081010-17031401	

Transmitter Tests (700 MHz)			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio		
	Offset From Center Frequency (kHz)		
	9.375	≥ 40 dB	Р
	15.625, 21.875, 37.5	≥ 60 dB	Р
	62.5, 87.5, 150, 250, 350	≥ 65 dB	Р
	>400 kHz to 12 MHz	≥ 75 dB	Р
	12 MHz to paired RX Band	≥ 75 dB	Р
	In the paired RX Band	≥ 100 dB	Р
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	Р
	Encoder Attack Time	≤ 100 ms	Р
2.2.14	Transmitter Throughput Delay	≤ 125 ms	Р
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	$2544 \; Hz < f_{dev} \le 3111 \; Hz$	Р
	Low Level Signal Deviation	848 Hz $< f_{dev} \le 1037 Hz$	Р
2.2.16	Modulation Fidelity	≤ 5% (Class A)	Р
2.2.18	Transient Frequency Behavior		
	Time Interval t₁ = 20 ms	∆f  ≤ 12.5 kHz	Р
	Time Interval t <sub>2</sub> = 50 ms	∆f  ≤ 6.25 kHz	Р
	Time Interval t <sub>3</sub> = 10 ms	∆f  ≤ 12.5 kHz	Р

## Receiver Tests (700/800 MHz) - Trunked

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-17031401 DTR-P25CAP081010-17031301

	Receiver Tests (700/800 MHz)				
Test Case	Test Case Description Requirement				
2.1.4	Reference Sensitivity	≤ -116 dBm (Class A)	P1		
2.1.5	Faded Reference Sensitivity	≤ -108 dBm (Class A)	P2		
2.1.6	Signal Delay Spread Capability	≥ 50 µs	P3		
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	P4		
2.1.8	Co-Channel Rejection	≤ 9 dB	Р		
2.1.9	Spurious Response Rejection	≥ 80 dB (Class A)	Р		
2.1.10	Intermodulation Rejection	≥ 75 dB (Class A)	Р		
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	Р		

# Transmitter Tests (800 MHz) - Trunked

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-17031401 DTR-P25CAP081010-17031301

Transmitter Tests (800 MHz)				
Test Case	se Description Requirement		Results	
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	Р	
2.2.12	Transmitter Power and Encoder Attack Time			
	Power Attack Time	≤ 50 ms	Р	
	Encoder Attack Time ≤ 100 ms		Р	
2.2.14	Transmitter Throughput Delay	≤ 125 ms	Р	
2.2.15	Frequency Deviation for C4FM			
	High Level Signal Deviation 2544 Hz < f <sub>dev</sub> ≤ 3		Р	
	Low Level Signal Deviation	$848~Hz < f_{dev} \leq 1037~Hz$	Р	
2.2.16	Modulation Fidelity	≤ 5% (Class A)	Р	
2.2.18	Transient Frequency Behavior			
	Time Interval t <sub>1</sub> = 20 ms	∆f  ≤ 12.5 kHz	Р	
	Time Interval t <sub>2</sub> = 50 ms	∆f  ≤ 6.25 kHz	Р	
	Time Interval t <sub>3</sub> = 10 ms	∆f  ≤ 12.5 kHz	Р	

## Transmitter Tests (700 MHz) - Trunked

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-17031401 DTR-P25CAP081010-17031301

Transmitter Tests (700 MHz)				
Test Case	Description Requirement		Results	
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio			
	Offset From Center Frequency (kHz)			
	9.375	≥ 40 dB	Р	
	15.625, 21.875, 37.5	≥ 60 dB	Р	
	62.5, 87.5, 150, 250, 350	≥ 65 dB	Р	
	>400 kHz to 12 MHz	≥ 75 dB	Р	
	12 MHz to Paired RX Band	≥ 75 dB	Р	
	In the Paired RX Band	≥ 100 dB	Р	
2.2.12	Transmitter Power and Encoder Attack Time			
	Power Attack Time	≤ 50 ms	Р	
	Encoder Attack Time	≤ 100 ms	Р	
2.2.14	Transmitter Throughput Delay	≤ 125 ms	Р	
2.2.15	Frequency Deviation for C4FM			
	High Level Signal Deviation	2544 Hz < f <sub>dev</sub> ≤ 3111 Hz	Р	
	Low Level Signal Deviation	848 Hz $< f_{dev} \le 1037 Hz$	Р	
2.2.16	Modulation Fidelity ≤ 5% (Class A)		Р	
2.2.18	Transient Frequency Behavior			
	Time Interval t₁ = 20 ms	∆f  ≤ 12.5 kHz	Р	
	Time Interval t <sub>2</sub> = 50 ms	∆f  ≤ 6.25 kHz	Р	
	Time Interval t <sub>3</sub> = 10 ms	∆f  ≤ 12.5 kHz	Р	

## Trunked Subscriber Unit Tests (700/800 MHz) - Trunked

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-17031401 DTR-P25CAP081010-17031301

Trunked Subscriber Unit Tests (700/800 MHz)				
Test Case	Case Description Requirement			
2.3.1	Trunking Control Channel Slot Times (45 ms slot) N7			
	Encode Attack Time	$2.00 \text{ ms} \le t \le 11.65 \text{ ms}$	Р	
	RF Power Attack Time	$0 \text{ ms} \le t \le 11.65 \text{ ms}$	Р	
	RF Power Turn Off Time	≤ 1.57 ms	Р	
2.3.2	Trunking Request Time	≤ 167.5 ms	Р	
2.3.3	Trunking Voice Access Time	500 ms	Р	
		(Manufacturer Specified)		
2.3.5	Transmitter Time to Key on a Traffic Channel			
	Short Channel Form	≤ 150.0 ms	Р	

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	Viking VP6430F2/F3 Portable Subscriber

Product	Detailed Test Report Identification
EF Johnson Technologies	DTR-P25CAP081010-17031001
Airbus / Tait	229AZUT17_2.1.3.3 Airbus TRUNKING SU IOT DTR 170208
Tait Limited	229AZUT17_2.1.3.3 TN9400 TRUNKING SU IOT DTR 170103
Motorola Solutions	DTR-P25CAP081010-17061402

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
2.2.1	Full Registration				
2.2.1.4.1	Test Case 1 - Valid Registration				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.1.4.2	Test Case 2 – Denied or Refused Registration				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.1.4.3	Test Case 3 - Unverified Registration				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.2	Group Voice Call				
2.2.2.4.1	Test Case 1 – Group Call Granted				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.2.4.2	Test Case 2 – Group Call Denied				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.2.4.3	Test Case 3 – Group Call Request Queued				
	Home Operation	Р	Р	Р	Р

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	Viking VP6430F2/F3 Portable Subscriber

Product	Detailed Test Report Identification
EF Johnson Technologies	DTR-P25CAP081010-17031001
Airbus / Tait	229AZUT17_2.1.3.3 Airbus TRUNKING SU IOT DTR 170208
Tait Limited	229AZUT17_2.1.3.3 TN9400 TRUNKING SU IOT DTR 170103
Motorola Solutions	DTR-P25CAP081010-17061402

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
2.2.3	Unit-To-Unit Voice Call				
2.2.3.4.1	Test Case 1 – Unit-To-Unit Call With Target Availability Check				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.3.4.2	Test Case 2 – Unit-To-Unit Call Target Availability Check Denied By Target				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.3.4.3	Test Case 3 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment after target availability check				
	Home Operation	Р	N/A 2	N/A 2	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.3.4.4	Test Case 4 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment before target availability check				
	Home Operation	N/A 1	N/A 2	N/A 2	N/A 1
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.3.4.5	Test Case 5 – Unit-To-Unit Call Without Target Availability Check				
	Home Operation	N/A 1	N/A 2	N/A 2	N/A 1
	Inter-System Operation	N1	N2	N3	N4

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
	Inter-WACN Operation	N1	N2	N3	N4
2.2.3.4.6	Test Case 6 – Unit-To-Unit Call Queued Without Target Availability Check				
	Home Operation	N/A 1	N/A 2	N/A 2	N/A 1
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.3.4.7	Test Case 7 – Unit-To-Unit Call Denied				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	Viking VP6430F2/F3 Portable Subscriber

Product	Detailed Test Report Identification
EF Johnson Technologies	DTR-P25CAP081010-17031001
Airbus / Tait	229AZUT17_2.1.3.3 Airbus TRUNKING SU IOT DTR 170208
Tait Limited	229AZUT17_2.1.3.3 TN9400 TRUNKING SU IOT DTR 170103
Motorola Solutions	DTR-P25CAP081010-17061402

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
2.2.4	Broadcast Voice Call				
2.2.4.4.1	Test Case 1 – Broadcast Voice Call				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.5	Affiliation				
2.2.5.4.1	Test Case 1 - Radio Permitted To Affiliate With New Group				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.5.4.2	Test Case 2 - Radio Denied Affiliation To New Group				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.6	Announcement Group Call				
2.2.6.4.1	Test Case 1 - Collection Of Talk Groups Receive Call				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.7	Emergency Alarm				
2.2.7.4.1	Test Case 1 - Emergency Alarm				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
	Inter-WACN Operation	N1	N2	N3	N4

Toot Idoutification	Dunalizat
Test Identification	Product
1 00t Idontiniodilon	

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	Viking VP6430F2/F3 Portable Subscriber

Product	Detailed Test Report Identification
EF Johnson Technologies	DTR-P25CAP081010-17031001
Airbus / Tait	229AZUT17_2.1.3.3 Airbus TRUNKING SU IOT DTR 170208
Tait Limited	229AZUT17_2.1.3.3 TN9400 TRUNKING SU IOT DTR 170103
Motorola Solutions	DTR-P25CAP081010-17061402

Test Case	Description	EF Johnson Atlas Trunked Infrastructure	Airbus/Tait Trunked Infrastructure	Tait Limited Trunked Infrastructure	Motorola Trunked Infrastructure
2.2.8	Emergency Group Call				
2.2.8.4.1	Test Case 1 - Emergency Call				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.10	Encryption				
2.2.10.4.1	Test Case 1 - Call Privacy For Encrypted Call				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4
2.2.11	Intra-Location Registration Area Roaming				
2.2.11.4.1	Test Case 1 – Idle Radio				
	Home Operation	Р	Р	Р	Р
	Inter-System Operation	N1	N2	N3	N4
	Inter-WACN Operation	N1	N2	N3	N4

## **Model Class Definition**

Applied to P25-CAB-CAI\_Test\_Req Mar 2010, 2.1.3.2

Model Class Name	Product Name, Definition, and Unique ID	Installed Options
Viking VP6430 Portable	Viking VP6430F2/F3 Portable Subscriber	<b>Firmware:</b> 8.18.12

#### **Test Case Result Definitions**

No Test Performed	
Test Does Not Apply to the Test Object	N/A
Test Object Meets Requirements	P (Pass)
Test Object Does Not Meet Requirements	F (Fail)
Test Object is Not Conclusive	I (Inconclusive)

#### **Comments**

N/A 1:	Test case 2.2.3.4.4, 2.2.3.4.5, 2.2.3.4.6 is not applicable for these infrastructures; see results of test 2.2.3.4.3.
N/A 2:	Test case 2.2.3.4.4, 2.2.3.4.5, 2.2.3.4.6 is not applicable for these infrastructures; see results of test 2.2.3.4.3.
N1:	EF Johnson infrastructure does not support Inter-System or Inter-WACN roaming.
N2:	Airbus/Tait infrastructure does not support Inter-System or Inter-WACN roaming.
N3	Tait Limited infrastructure does not support Inter-System or Inter-WACN roaming.
N4:	Motorola infrastructure does not support Inter-System or Inter-WACN roaming.
P1:	VP 6430 700/800 subscriber passes Reference Sensitivity (≤ -116 dBm) specification for C4FM (Non-Simulcast) and Simulcast modulations.
P2:	VP 6430 700/800 subscriber passes Faded Reference Sensitivity (≤ -108 dBm) specification for C4FM (Non-Simulcast) and Simulcast modulations.
P3:	VP 6430 700/800 subscriber passes Signal Delay Spread Capability specification for C4FM (Non-Simulcast) (≥ 50 µs) and Simulcast modulations (≥ 80 µs).
P4:	VP 700/800 subscriber passes Adjacent Channel Rejection (≥ 60 dB) specification for C4FM (Non-Simulcast) and Simulcast modulations.

The information contained herein has been provided by the manufacturer of the product with permission to make the information publicly available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS". DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITTNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute an endorsement by or recommendation from DHS.

**OMB NO:** 1640-0015

**EXPIRATION DATE:** 06/30/2019

#### **Burden Statement**

An agency may not consider or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and expiration date. The control number for this collection is 1640-0015 and this form will expire on 06/30/2019. The estimated average time to complete this form is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528.

DHS FORM 10044 - June 2009