#### **Test Item Description**

Manufacturer	EF Johnson Technologies	
Manufacturer Contact	Randy O'Connor (972) 819-0911	
Product Name Viking VP5330 F5/F6 UHF Portable Subscriber Unit		
Installed Options	Full and Limited Keypad, AES/DES KWD-AE30 Encryption Module Installed	
Vocoder Identification	Enhanced Full Rate	

#### **Test Description**

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability

#### Laboratory Information

Laboratory	Details	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)	
Date(s) of Test	August 2, 2016	
Date of Issue	August 2, 2016	

Laboratory	Details	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)	
Date(s) of Test	August 17, 2016	
Date of Issue	August 17, 2016	

Laboratory	Details	
P25 CAP Laboratory Code P25CAP081017 (Harris)		
Date(s) of Test	August 23, 2016	
Date of Issue	August 23, 2016	

## **Informative References**

Date	Title
Mar 2010	P25-CAB-CAI_TEST_REQ – March 2010

#### Other Devices Tested with Viking VP5330F5/F6 Portable Subscriber Unit

Manufacturer	Product Name, Definition, and Unique ID	Installed Options	
EF Johnson	ATLAS Trunked Infrastructure	TSNI 1.3.2_14	
Harris	P25 Trunked Infrastructure	Release SR10A.2	
Motorola Solutions	Astro Trunked Infrastructure	Release 25.7.16	

## **Receiver Tests – Conventional**

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance	DTR-P25CAP081010-16081001

Receiver Tests			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	$\leq$ -116 dBm (Class A	P1
2.1.5	Faded Reference Sensitivity	$\leq$ -108 dBm (Class A)	P2
2.1.6	Signal Delay Spread Capability	≥ 50 µs	P3
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	Р
2.1.9	Spurious Response Rejection	≥ 80 dB (Class A)	Р
2.1.10	Intermodulation Rejection	≥ 75 dB (Class A)	Р
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	Р
2.1.17	Late Entry Unsquelch Delay		
	No Talk Group or Encryption	≤ 125 ms	Р
	Talk Group Only	≤ 370 ms	Р
	Encryption Only	≤ 370 ms	Р
	Both Talk Group and Encryption	≤ 460 ms	Р
2.1.18	Receiver Throughput Delay	≤ 125 ms	Р

# **Transmitter Tests – Conventional**

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase 1 Common Air Interface Conventional Subscriber Unit Performance	DTR-P25CAP081010-16081001

Transmitter Tests			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	Р
2.2.12	Transmitter Power and Encoder Attack Time		
	Power Attack Time	≤ 50 ms	Р
	Encoder Attack Time	≤ 100 ms	Р
2.2.14	Transmitter Throughput Delay	≤ 125 ms	Р
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	2544 Hz < $f_{dev} \leq$ 3111 Hz	Р
	Low Level Signal Deviation	848 Hz $<$ f <sub>dev</sub> $\leq$ 1037 Hz	Р
2.2.16	Modulation Fidelity	$\leq$ 5% (Class A)	Р
2.2.18	Transient Frequency Behavior		
	Time Interval t <sub>1</sub> = 10 ms	$ \Delta f  \le 12.5 \text{ kHz}$	Р
	Time Interval t <sub>2</sub> = 25 ms	$ \Delta f  \le 6.25 \text{ kHz}$	Р
	Time Interval t <sub>3</sub> = 10 ms	$ \Delta f  \le 12.5 \text{ kHz}$	Р

## **Receiver Tests- Trunked**

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-16081001 DTR-P25CAP081010-16081703

Receiver Tests			
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	$\leq$ -116 dBm (Class A)	P1
2.1.5	Faded Reference Sensitivity	$\leq$ -108 dBm (Class A)	P2
2.1.6	Signal Delay Spread Capability	≥ 50 µs	P3
2.1.7	Adjacent Channel Rejection	$\geq$ 60 dB (Class A)	P4
2.1.8	Co-Channel Rejection	≤ 9 dB	Р
2.1.9	Spurious Response Rejection	$\geq$ 80 dB (Class A)	Р
2.1.10	Intermodulation Rejection	$\geq$ 75 dB (Class A)	Р
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	Р

## Transmitter Tests – Trunked

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-16081001 DTR-P25CAP081010-16081703

	Transmitter Tests			
Test Case	Description	Requirement	Results	
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	Р	
2.2.12	Transmitter Power and Encoder Attack Time			
	Power Attack Time	≤ 50 ms	Р	
	Encoder Attack Time	≤ 100 ms	Р	
2.2.14	Transmitter Throughput Delay	≤ 125 ms	Р	
2.2.15	Frequency Deviation for C4FM			
	High Level Signal Deviation	$2544~Hz < f_{dev} \leq 3111~Hz$	Р	
	Low Level Signal Deviation	$848 \text{ Hz} < f_{\text{dev}} \leq 1037 \text{ Hz}$	Р	
2.2.16	Modulation Fidelity	$\leq$ 5% (Class A)	Р	
2.2.18	Transient Frequency Behavior			
	Time Interval t <sub>1</sub> = 10 ms	∆f  ≤ 12.5 kHz	Р	
	Time Interval t <sub>2</sub> = 25 ms	$ \Delta f  \le 6.25 \text{ kHz}$	Р	
	Time Interval t <sub>3</sub> = 10 ms	∆f  ≤ 12.5 kHz	Р	

### **Trunked Subscriber Unit Tests – Trunked**

Test Identification	Detailed Test Report Identification
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Performance	DTR-P25CAP081010-16081001 DTR-P25CAP081010-16081703

Trunked Subscriber Unit Tests			
Test Case	Description	Requirement	Results
2.3.1	Trunking Control Channel Slot Times (45 ms slot) N7		
	Encode Attack Time	$2.00\ ms \leq t \leq 11.65\ ms$	Р
	RF Power Attack Time	$0 \text{ ms} \le t \le 11.65 \text{ ms}$	Р
	RF Power Turn Off Time	≤ 1.57 ms	Р
2.3.2	Trunking Request Time	≤ 167.5 ms	Р
2.3.3	Trunking Voice Access Time	500 ms	Р
		(Manufacturer Specified)	
2.3.5	Transmitter Time to Key on a Traffic Channel		
	Short Channel Form	≤ 150.0 ms	Р

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	EF Johnson Viking VP5330F5/F6 UHF Portable Subscriber

Product	Detailed Test Report Identification	
Motorola Solutions ASTRO Trunked Infrastructure	DTR-P25CAP081010-16080202	
EF Johnson Atlas Trunked Infrastructure	DTR-P25CAP081010-16080301	
Harris Infrastructure	DTP-P25CAP081010-1121211E01	

Test Case	Description	Motorola Solutions ASTRO Trunked Infrastructure	EF Johnson Atlas Trunked Infrastructure	Harris Trunked Infrastructure
2.2.1	Full Registration			
2.2.1.4.1	Test Case 1 - Valid Registration			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.1.4.2	Test Case 2 – Denied or Refused Registration			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.1.4.3	Test Case 3 - Unverified Registration			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.2	Group Voice Call			
Z.2.2.4.1 Test Case 1 – Group Call Granted				
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.2.4.2	Test Case 2 – Group Call Denied			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.2.4.3	Test Case 3 – Group Call Request Queued			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	EF Johnson Viking VP5330F5/F6 UHF Portable Subscriber

Product	Detailed Test Report Identification	
Motorola Solutions ASTRO Trunked Infrastructure	DTR-P25CAP081010-16080202	
EF Johnson Atlas Trunked Infrastructure	DTR-P25CAP081010-16080301	
Harris Infrastructure	DTP-P25CAP081010-1121211E01	

Test Case	Description	Motorola Solutions ASTRO Trunked Infrastructure	EF Johnson Atlas Trunked Infrastructure	Harris Trunked Infrastructure
2.2.3	Unit-To-Unit Voice Call			
2.2.3.4.1	Test Case 1 – Unit-To-Unit Call With Target Availability Check			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.3.4.2	Test Case 2 – Unit-To-Unit Call Target Availability Check Denied By Target			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.3.4.3	Test Case 3 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment after target availability check			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.3.4.4	Test Case 4 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment before target availability check			
	Home Operation	N/A 1	N/A 1	N/A 1
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.5	Test Case 5 – Unit-To-Unit Call Without Target Availability Check			
	Home Operation	N2	N2	N2
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4

Test Case	Description	Motorola Solutions ASTRO Trunked Infrastructure	EF Johnson Atlas Trunked Infrastructure	Harris Trunked Infrastructure
2.2.3.4.6	Test Case 6 – Unit-To-Unit Call Queued Without Target Availability Check			
	Home Operation	N2	N2	N2
	Inter-System Operation	N1	N3	N4
	Inter-WACN Operation	N1	N3	N4
2.2.3.4.7	Test Case 7 – Unit-To-Unit Call Denied			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	EF Johnson Viking VP5330F5/F6 UHF Portable Subscriber

Product	Detailed Test Report Identification
Motorola Solutions ASTRO Trunked Infrastructure	DTR-P25CAP081010-16080202
EF Johnson Atlas Trunked Infrastructure	DTR-P25CAP081010-16080301
Harris Infrastructure	DTP-P25CAP081010-1121211E01

Test Case	Description	Motorola Solutions ASTRO Trunked Infrastructure	EF Johnson Atlas Trunked Infrastructure	Harris Trunked Infrastructure	
2.2.4	Broadcast Voice Call				
2.2.4.4.1	Test Case 1 – Broadcast Voice Call	Test Case 1 – Broadcast Voice Call			
	Home Operation	Р	Р	Р	
	Inter-System Operation	N1	N3	Р	
	Inter-WACN Operation	N1	N3	N5	
2.2.5	Affiliation				
2.2.5.4.1	Test Case 1 - Radio Permitted To Affiliate With New Group				
	Home Operation	Р	Р	Р	
	Inter-System Operation	N1	N3	Р	
	Inter-WACN Operation	N1	N3	N5	
2.2.5.4.2	Test Case 2 - Radio Denied Affiliation To New Group				
	Home Operation	Р	Р	Р	
	Inter-System Operation	N1	N3	Р	
	Inter-WACN Operation	N1	N3	N5	
2.2.6	Announcement Group Call				
2.2.6.4.1	Test Case 1 - Collection Of Talk Groups Receive Call				
	Home Operation	Р	Р	Р	
	Inter-System Operation	N1	N3	Р	
	Inter-WACN Operation	N1	N3	N5	
2.2.7	Emergency Alarm				
2.2.7.4.1	Test Case 1 - Emergency Alarm				
	Home Operation	Р	Р	Р	
	Inter-System Operation	N1	N3	Р	
	Inter-WACN Operation	N1	N3	N5	

Test Identification	Product
P25-CAB-CAI_TEST_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase 1 Common Air Interface Trunked Subscriber Unit Interoperability	EF Johnson Viking VP5330F5/F6 UHF Portable Subscriber

Product	Detailed Test Report Identification	
Motorola Solutions ASTRO Trunked Infrastructure	DTR-P25CAP081010-16080202	
EF Johnson Atlas Trunked Infrastructure	DTR-P25CAP081010-16080301	
Harris Infrastructure	DTP-P25CAP081010-1121211E01	

Test Case	Description	Motorola Solutions ASTRO Trunked Infrastructure	EF Johnson Atlas Trunked Infrastructure	Harris Trunked Infrastructure
2.2.8	Emergency Group Call			
2.2.8.4.1	Test Case 1 - Emergency Call			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.10	Encryption			
2.2.10.4.1	Test Case 1 - Call Privacy For Encrypted Call			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5
2.2.11	Intra-Location Registration Area Roaming			
2.2.11.4.1	Test Case 1 – Idle Radio			
	Home Operation	Р	Р	Р
	Inter-System Operation	N1	N3	Р
	Inter-WACN Operation	N1	N3	N5

## Model Class Definition

Applied to P25-CAB-CAI\_Test\_Req Mar 2010, 2.1.3.2

Model Class Name	Product Name, Definition, and Unique ID	Installed Options
Viking VP5330 Portable	EF Johnson Viking VP5330F5/F6 UHF Portable Subscriber	Firmware: 8.16.3 Firmware: 8.16.6

# **Test Case Result Definitions**

No Test Performed	
Test Does Not Apply to the Test Object	N/A
Test Object Meets Requirements	P (Pass)
Test Object Does Not Meet Requirements	F (Fail)
Test Object is Not Conclusive	I (Inconclusive)

### Comments

N/A 1:	N/A 1: Test case 2.2.3.4.4 is not applicable for these infrastructures; see results of test 2.2.3.4.3.
N1:	Motorola infrastructure does not support Inter-System or Inter-WACN roaming.
N2:	Test Cases 2.2.3.4.5 and 2.2.3.4.6 are not supported by EF Johnson
N3:	EF Johnson infrastructure does not support Inter-System or Inter-WACN roaming.
N4:	Not supported by EF Johnson Subscriber Unit
N5:	Harris infrastructure does not support Inter-WACN roaming.
P1:	EF Johnson VP 5330 subscriber passes Reference Sensitivity ( $\leq$ -116 dBm) specification for C4FM (Non-Simulcast) and Simulcast modulations.
P2:	EF Johnson VP 5330 subscriber passes Faded Reference Sensitivity ( $\leq$ -108 dBm) specification for C4FM (Non-Simulcast) and Simulcast modulations.
P3:	EF Johnson VP 5330 subscriber passes Signal Delay Spread Capability specification for C4FM (Non-Simulcast) ( $\geq$ 50 µs) and Simulcast modulations ( $\geq$ 80 µs).
P4:	EF Johnson VP 5330 subscriber passes Adjacent Channel Rejection ( $\geq$ 60 dB) specification for C4FM (Non-Simulcast) and Simulcast modulations.

The information contained herein has been provided by the manufacturer of the product with permission to make the information publicly available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS". DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITTNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute an endorsement by or recommendation from DHS.

OMB NO: 1640-0015

#### **EXPIRATION DATE: 06/30/2019**

#### **Burden Statement**

An agency may not consider or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and expiration date. The control number for this collection is 1640-0015 and this form will expire on 06/30/2019. The estimated average time to complete this form is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528.

DHS FORM 10044 - June 2009