

P25 Mission Critical

# Viking VP6000

VHF · UHF · 70/800 MHz · SN/SZ  
P25 Phase 1 & 2

The KENWOOD Viking 6000 series portable is specifically designed for today's public safety agencies with advanced features and ergonomics to meet the first responder's mission critical operational needs.



## Features

Mixed protocol operation (P25 Phase 1 & 2 Trunking, P25 Conventional, SN/SZ, FM Analog)

Mixed protocol zones (each channel in a zone can be from a different system)

1024 channels (2048 option)

Public safety ergonomics: flare grip for control, large glove friendly knobs, large emergency button

1 Watt audio output for high noise environments

Voice annunciation & custom announcement creation

Fully ruggedized - IP67/68 & MIL-STD-810 C/D/E/F/G

Full key models (w/ numeric keypad)

Built-in GPS receiver/antenna for enhanced awareness<sup>1</sup>

MDC-1200 & GE-Star signaling

P25 Authentication

Bluetooth<sup>®</sup>

Man Down

Encryption

- ARC4™ software encryption; compatible w/Motorola ADP™
- P25/TIA defined: AES-256
- DES-OFB
- Over-the-Air-Rekeying (OTAR)

<sup>1</sup>Refer to the Viking VP6000 operating manual for detailed requirements & conditions for proper GPS operation.

## User Selectable Color Themes

Multi-line text

Top flip display changes text orientation for viewing while in holster

Multiple visual indicators including battery health & signal strength

Backlight changes for event identification

Day & night user selectable display options (8 themes available)



Day - High Contrast



Night - High Contrast

## Compatible with Multiple P25 Systems

ATLAS<sup>®</sup> P25 Phase 1 and Phase 2 System

Motorola<sup>®</sup> Systems

- Motorola Astro<sup>®</sup> 25 - P25 Phase 1 & Phase 2
- Motorola Astro<sup>®</sup> SmartNet<sup>®</sup>/SmartZone<sup>®</sup>

Harris VIDA<sup>®</sup> - P 25 Phase 1 & Phase 2

Airbus (formerly Cassidian) VESTA<sup>™</sup> Radia - P25 Phase 1 & Phase 2

## Accessories

Complete line of accessories including microphones, speakers & antennas. Download the accessory catalog at [www.efjohnson.com/products/accessories](http://www.efjohnson.com/products/accessories).

We combine P25 design expertise with recognized quality & reliability along with advanced technology to make KENWOOD Viking radios simple to use & maintain.



### Perpetual Software Licensing

Adds greater value to your radios by extending the life of the software into your next hardware platform — you own the software option forever, and your licenses are simple to manage with our cloud-based tool — Vault™.



### Armada<sup>®</sup> Fleet Management

Update radios in a group rather than one at a time. One template programs both portables & mobiles. Supports either direct computer connection or Over-the-Air Programming (OTAP). Elite battery management enables wireless tracking of battery fleet.



### TrueVoice<sup>™</sup> Noise Cancellation

Software-based noise cancellation automatically filters out noise source frequencies and eliminates the need for extra configuration. Works in analog or digital mode and with any accessory.

# VP6230/6330/6430 Portable Specifications

General		VP6230	VP6330	VP6430
Frequency Range		136-174 MHz (FCC ID K44431400)	Type 1: 450-520 MHz (FCC ID K44431500) Type 2: 380-470 MHz (FCC ID K44431501)	RX: 763-776, 851-870 MHz TX: 763-776, 793-806, 806-825, 851-870 MHz (FCC ID ALH442000)
Max. Channels Per Radio		1024 (2048 option)		
Number of Zones		255		
Max. Channels Per Zone		255		
Channel Spacing	Analog	12.5/15/20/25*/30* kHz	12.5/25* kHz	12.5/25 kHz
	Digital	12.5 kHz	12.5 kHz	12.5 kHz
Power Supply		7.5 V DC ±20%		
Operating Temperature		-22 °F to +140 °F (-30 °C to +60 °C)		
Frequency Stability		±1.5 ppm	±1.5 ppm	±1.5 ppm
Case		Polycarbonate - black or high visibility (additional fee)		
Dimensions W(Top/Bot- tom) x H x D Projections not included	KNB-L2 (2,600 mAh)	2.76/2.28 x 5.90 x 1.73 in. (70.0/58.0 x 149.8 x 44.0 mm)		
	KNB-L3 (3,400 mAh)	2.76/2.28 x 5.90 x 1.94 in. (70.0/58.0 x 149.8 x 49.4 mm)		
Weight with Battery	KNB-L2 (2,600 mAh)	171 oz (484.5 g)		
	KNB-L3 (3,400 mAh)	18.6 oz (527.5 g)		
Receiver		VP6230	VP6330	VP6430
Sensitivity	P25 Digital (5% BER)	-119 dBm		
	Analog (12 dB SINAD)	-119 dBm		
Selectivity	P25 Digital	60 dB		
	Analog @ 12.5 kHz	65 dB		
	Analog @ 25 kHz	73 dB		
Intermodulation		73 dB		75 dB
Spurious Rejection		80 dB	75 dB	
Audio Distortion		3%		
Audio Output Power		500 mW/8 Ω (3% Distortion)/1,000 mW/8 Ω (5% Distortion)		
Transmitter		VP6230	VP6330	VP6430
RF Output Power		1W/6W	1W/5W	1W/3W
Spurious Emission		-70 dB		
FM Hum & Noise	Analog @ 12.5 kHz	40 dB		
	Analog @ 25 kHz	45 dB		
Audio Distortion		2%		
Emission Designator		16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W		16K0F3E, 14K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W

MIL Standard	810G
Low Pressure	500.5/ I, II
High Temperature	501.5/ I, II
Low Temperature	502.5/ I, II
Temp. Shock	503.5/ I
Solar Radiation	505.5/ I
Rain	506.5/ I, III
Humidity	507.5/ II
Salt Fog	509.5
Dust	510.5/ I
Vibration	514.6/ I
Immersion	512.5/ I
Shock	516.6/ I, IV

Encryption Options	
Supported Encryption	AES, DES-OFB, ARC4
Encryption Key/ Radio	126 Common Key Reference (CKR), 126 Physical Identifier (PID), Compatible w/ Motorola Key Variable Loader
Encryption Frame Re-sync Interval	P25 CAI 360 MSEC
Encryption Keying	External Key Loader, OTAR
Mode	OFB-Output Feedback
Encryption Type	Digital
Key Erasure	Keyboard Command
Standards	FIPS 46-3, FIPS 81, FIPS 140-2, FIPS 197

Hazardous Location Standard	
Certification Lab	CSA Group
Standard Applied	ANSI/TIA 4950-A-2014, UL913 5th Edition & ANSI/ISA-12.12.01-2011
Classification Rating	Intrinsically Safe: Classes I, II, III, Division 1, Groups D, E, F, G Non-incendive: Class I, Division 2, Groups A, B, C, D

Accessories	
Approved Battery	KNB-LS5 (USA), KNB-LS6 (Canada)
Approved Speaker Microphones	KMC-54WDM

International Protection Standard	
Dust & Water	IP54, IP55
Immersion	IP67**, IP68***

\* 25 and 30 kHz are not included in the models sold in the USA or US territories.  
 \*\* IP67/IP68 - Must have the Speaker Mic UDC connector or UDC protector connected.  
 \*\*\* IP68 = 1m/2H

Specifications shown are typical and subject to change without notice Please check the website for the latest version.  
 V072718 © Copyright 2018 EF Johnson Technologies, Inc. (E.F. Johnson Company is operating entity)  
 The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.

**EF Johnson Technologies, Inc.**  
 a JVCKENWOOD Company  
 1440 Corporate Drive, Irving, TX 75038-2401  
 Phone: 800.328.3911 · efjohnson.com